

Air Data Feature Comparison Chart

MEASUREMENT DATA

	1811 Series	DPS350	DPS450	DPS500
R.V.S.M. Accuracy	-	S	S	S
Aneroid Instruments (Analog)	S	-	-	-
Correction Cards	S	-	-	-
Altitude up to 55,000 ft	O	S	S	-
Altitude up to 100,000 ft	-	-	-	S
Airspeed up to 650kts	O	S	S	-
Airspeed up to 850kts	-	-	-	S
Airspeed up to 1000kts	-	-	-	O
Vertical Speed to 6000 ft/min	O	S	S	S
Vertical Speed above 6000 ft/min	O*	S	S	S
Transducers	O*	S	S	S

DISPLAY CHARACTERISTICS

	1811 Series	DPS350	DPS450	DPS500
Analog instruments	S	-	-	-
Digital LCD Display	O*	S	S	S
Menu driven displays	O*	S	S	S
Airspeed, knots	S	S	S	S
Altitude, feet	S	S	S	S
Rate of Climb, feet per minute	O	S	S	S
Mach	O*	S	S	S
Airspeed, kilometer per hour	O*	S	S	S
Altitude, meters	O*	S	S	S
Rate of Climb, meters per minute	O*	S	S	S
EPR: Pt / Ps	O*	S	S	S
Unit measurement in millibars	O*	S	S	S
Unit measurement in inches of mercury	O*	S	S	S
Unit measurement in psi	O*	S	S	S
Unit measurement in millimeters of mercury	-	-	S	S
Unit measurement in inches of water	-	-	S	S
Unit measurement in hectopascals	-	-	S	S
Unit measurement in kilopascal	-	-	S	S
True Airspeed, knots & kilometer per hour	-	-	-	S

CONTROL FEATURES

	1811 Series	DPS350	DPS450	DPS500
Manual needle valve control	S	S	-	-
Manual differential regulators	-	-	-	-
Semi-automatic microprocessor control	-	S	-	-
Leak measure facility	O*	S	S	S
Full automatic microprocessor control	-	-	S	S
Keyboard data entry	-	-	S	S
Controlled climb / decent rate	-	-	S	S
Automatic "Go to ground" function	-	-	S	S
Auto Intervention (for excessive leaks)	-	-	S	S
Remote control	-	-	O	S
Remote control (via DPS500) line switching unit	-	-	-	O
Manually operated lid Ps/Pt manifold	-	-	O	O

S = Standard Feature O = Option - = Not available
* 1811 Series with DAS650 & DALTS5 option

Barfield Inc.
4101 NW 29th Street.
Miami, FL 33142
Phone Line: (305) 894-5400
Fax Line: (305) 894-5401