

2471F Megohmmeter

The 2471F megohmmeter is designed to check the insulation breakdown in a variety of applications requiring a high voltage but low current. The 2471F Megohmmeter provides the operator with a simple, rugged, portable analog unit with selectable test voltages of 45, 100, 200 and 500 VDC. The range of test voltages allows the operator to quickly test and pinpoint insulation breakdown over a range of 0.5 to 1000 Megohm. The tester is battery operated, with no warm-up time necessary allowing completely portable, fast, reliable checks of antenna bonding, shielding, static wicks, ground straps, etc.

Current limiting circuitry provides safe, ABSOLUTELY SHOCKPROOF operation. The tester is completely user safe even on the 500 volt range since the maximum allowable test currents are well below human sensitivities. The 2471F is also protected from damage caused by inadvertent connection of the probes across an energized circuit. AC or DC voltages up to 300 volts can be safely applied.

A single four-inch meter scale, increasing from zero at the left to infinity at the right, is incremented from .5 to 1,000 megohms. A push-button on the high potential test probe provides for conveniently activating the instrument and allows the technician access to tight testing areas without fear of arcing. Solid state circuitry provides the means for size reduction, high sensitivity, and dependability. The meter is a ruggedized taut-band suspension type, which eliminates the need for pivots and jewels. The high potential probe is shield-guarded so that stray leakage through lead insulation will not affect the measurement accuracy.

Specifications

Test potential (Volts)	Max. Current (μ A)
45 \pm 10%	3
100 \pm 10%	6
200 \pm 10%	12
500 \pm 10%	30



Features

- Hand-held, portable, rugged, durable and lightweight
- Push to test probe button activation
- Simple forward reading scale
- Absolutely no shock hazards
- Sensitive operational amplifier
- Powered from common "C" and "AA" batteries with auto-off feature to conserve batteries
- Solid-state circuitry

2471F Dimensions

	in.	cm.
Height	8.0	20.3
Width	6.0	15.2
Depth	4.75	12.1
	lbs.	kg.
Weight	3.8	1.7

Call us regarding export restrictions

Copyright © 2014 Barfield Inc. All Rights Reserved.

Barfield, Inc.
4101 NW 29th Street, Miami, FL 33142
Tel: +1 305-894-5400 Fax: +1 305-894-5401
www.barfieldinc.com